

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 July 2003 (31.07.2003)


PCT

(10) International Publication Number
WO 03/063065 A1

- (51) International Patent Classification⁷: **G06K 9/00**
- (21) International Application Number: PCT/GB03/00042
- (22) International Filing Date: 8 January 2003 (08.01.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0201080.9 18 January 2002 (18.01.2002) GB
- (71) Applicant (for all designated States except US): **QINETIQ LIMITED** [GB/GB]; 85 Buckingham Gate, London SW1E 6PD (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **SWATTON, Stewart, Nathan, Ridgley** [GB/GB]; QINETIQ LIMITED, St Andrews Road, Malvern, Worcestershire WR14 3PS (GB).
- (74) Agent: **KNIGHT, Samuel**; IP QinetiQ Formalities, Cody Technology Park, A4 Building Ively Road, Farnborough, Hampshire GU14 0LX (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:**
— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: OPTICAL BIOMETRIC SENSOR WITH PLANAR WAVEGUIDE



(57) Abstract: A biometric sensor (10) comprises a detector array (12) and a planar slab waveguide (16). Diode laser arrays (18, 20) are arranged to couple light into the planar slab waveguide. A ridge of an individual's fingerprint or palmprint, when in contact with the planar slab waveguide at a point of contact therewith, causes a fraction of the light within the waveguide to become unguided at the point of contact, said fraction being detected by the detector array. The sensor has reduced complexity compared to similar sensors employing fibre-optic faceplates and also provides for removal of noise in fingerprint images formed by the sensor, said noise arising from accumulation of dirt or grease on the sensor.

WO 03/063065 A1